

DECLARATION OF PERFORMANCES

DOP N°001-2018

1. Unique identification code of the product-type: **CO3-S-01**

Commercial name : **HYBRIS, ALVEOL'R, CELLUL'R ou THERMO AIR**

2. Intended use/es:

Building thermal insulation product with external surface acting as a vapour control layer

3. Manufacturer :

ACTIS S.A.

30 Avenue de Catalogne

F-11300 LIMOUX

www.actis-isolation.com

4. Authorised representative: **Non applicable**

5. System/s of AVCP: **Système 3**

6. a/ Harmonised standard : Non applicable

b/ European Assessment Document: EAD-004007-00-1201 (Décembre 2015)

European Technical Assessment: **ETA -18/0357 délivré le 22/04/2018**

Technical Assessment Body: CSTB Centre Scientifique et Technique du Bâtiment

Notified body/ies:

- **VTT Technical Research Centre of Finland, n°0809**
- **LNE Laboratoire National de et d'Essais (NB0071)**

DECLARATION OF PERFORMANCES

DOP N°001-2018

7. Declared performance/s:

Essential characteristics	Standard	Performances																																																																	
		HYBRIS, ALVEOL'R, CELLUL'R ou THERMO AIR																																																																	
Fire reaction Euroclass characteristics		F																																																																	
Water vapour transmission	EN 12572	Sd > 90 m																																																																	
Thickness range	EN 823	50 à 205 mm																																																																	
Declared core thermal resistance	EN 12667	<p>Non ventilated air gap thermal resistance calculation according to EN ISO 6946</p> <table border="1"> <thead> <tr> <th>Thickness</th> <th>R Core</th> <th>R + 1 air gap</th> <th colspan="2">R + 2 air gaps</th> </tr> </thead> <tbody> <tr> <td>50 mm</td> <td>1.5</td> <td>2.10</td> <td>2,70</td> <td>m².K/W</td> </tr> <tr> <td>60 mm</td> <td>1,8</td> <td>2,40</td> <td>3,00</td> <td>m².K/W</td> </tr> <tr> <td>75 mm</td> <td>2,25</td> <td>2.85</td> <td>3,45</td> <td>m².K/W</td> </tr> <tr> <td>90 mm</td> <td>2,7</td> <td>3.30</td> <td>3.90</td> <td>m².K/W</td> </tr> <tr> <td>105 mm</td> <td>3,15</td> <td>3,75</td> <td>4,35</td> <td>m².K/W</td> </tr> <tr> <td>125 mm</td> <td>3.75</td> <td>4,35</td> <td>4.95</td> <td>m².K/W</td> </tr> <tr> <td>140 mm</td> <td>4.20</td> <td>4,80</td> <td>5,40</td> <td>m².K/W</td> </tr> <tr> <td>155 mm</td> <td>4,65</td> <td>5,25</td> <td>5,85</td> <td>m².K/W</td> </tr> <tr> <td>170 mm</td> <td>5.15</td> <td>5,75</td> <td>6,35</td> <td>m².K/W</td> </tr> <tr> <td>185 mm</td> <td>5,60</td> <td>6,20</td> <td>6,80</td> <td>m².K/W</td> </tr> <tr> <td>195 mm</td> <td>5,9</td> <td>6,50</td> <td>7,10</td> <td>m².K/W</td> </tr> <tr> <td>205 mm</td> <td>6,20</td> <td>6.80</td> <td>7,60</td> <td>m².K/W</td> </tr> </tbody> </table> <p>air gap 20 mm , horizontal flux in a 20 °C room and external air at 0°C</p>	Thickness	R Core	R + 1 air gap	R + 2 air gaps		50 mm	1.5	2.10	2,70	m ² .K/W	60 mm	1,8	2,40	3,00	m ² .K/W	75 mm	2,25	2.85	3,45	m ² .K/W	90 mm	2,7	3.30	3.90	m ² .K/W	105 mm	3,15	3,75	4,35	m ² .K/W	125 mm	3.75	4,35	4.95	m ² .K/W	140 mm	4.20	4,80	5,40	m ² .K/W	155 mm	4,65	5,25	5,85	m ² .K/W	170 mm	5.15	5,75	6,35	m ² .K/W	185 mm	5,60	6,20	6,80	m ² .K/W	195 mm	5,9	6,50	7,10	m ² .K/W	205 mm	6,20	6.80	7,60	m ² .K/W
Thickness	R Core	R + 1 air gap	R + 2 air gaps																																																																
50 mm	1.5	2.10	2,70	m ² .K/W																																																															
60 mm	1,8	2,40	3,00	m ² .K/W																																																															
75 mm	2,25	2.85	3,45	m ² .K/W																																																															
90 mm	2,7	3.30	3.90	m ² .K/W																																																															
105 mm	3,15	3,75	4,35	m ² .K/W																																																															
125 mm	3.75	4,35	4.95	m ² .K/W																																																															
140 mm	4.20	4,80	5,40	m ² .K/W																																																															
155 mm	4,65	5,25	5,85	m ² .K/W																																																															
170 mm	5.15	5,75	6,35	m ² .K/W																																																															
185 mm	5,60	6,20	6,80	m ² .K/W																																																															
195 mm	5,9	6,50	7,10	m ² .K/W																																																															
205 mm	6,20	6.80	7,60	m ² .K/W																																																															
Declared emissivity	EN 16012	≤ 0,06 / 0,1																																																																	

ACTIS

INNOVER POUR MIEUX ISOLER

Avenue de Catalogne
11300 Limoux

TÉL. : (+33) 04 68 31 31 31 - FAX : (+33) 04 68 31 94 97
infos@actis-isolation.com

www.actis-isolation.com

DECLARATION OF PERFORMANCES

DOP N°001-2018

Essential characteristics		Standard	Performances
		HYBRIS, ALVEOL'R, CELLUL'R ou THERMO AIR	
Biological resistance		NPD	
Chemical additives retention		NPD	
Corrosion resistance		NPD	
Compressive creep		NPD	
Pointwise load strength		NPD	
Peel strength of tape before/after ageing		EN ISO 11339	> 20 N/100 mm
Tensile strength before / after ageing	Product resistance	EN 1608	> 45 kPa
	Product resistance with tape		> 80 N/100 mm
Tensile strength perpendicular to faces		NPD	
Resistance to tearing, nail shank before/after ageing		EN 12310-1	> 150 N
Surface mass (density)		EN 1602	9.5 ± 1 kg/m ³
Water uptake		NPD	
Compressive strength		NPD	
Dimensional stability		NPD	
Emission of dangerous substances		None	

DECLARATION OF PERFORMANCES

DOP N°001-2018

8. Appropriate Technical Documentation and/or Specific Technical Documentation: Non applicable

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Laurent THIERRY
Chairman / Managing Director

At Limoux, on 06/09/2018



ACTIS

INNOVER POUR MIEUX ISOLER

Avenue de Catalogne
11300 Limoux

TÉL. : (+33) 04 68 31 31 31 - FAX : (+33) 04 68 31 94 97
infos@actis-isolation.com

www.actis-isolation.com