## DECLARATION OF PERFORMANCE DOP N°005-2018-03

1. Unique identification code of the product-type: 87-001

Commercial Name: HCONTROL HYBRID

2. Intended use/es:

Plastic and rubber vapour control layer (type A)

3. Manufacturer:

ACTIS S.A.
30, Avenue de Catalogne
F-11300 LIMOUX
www.actis-isolation.com

4. Authorised representative: Not applicable

5. System/s of AVCP: System 3

6. Harmonised standard:

EN 13984: 2013

Notified body/ies:

VTT Technical Research Centre of Finland, notified body no. 0809

7. Declared performance/s:



Avenue de Catalogne 11300 Limoux

## DECLARATION OF PERFORMANCE DOP N°005-2018-03

Essential characteristics		Performances	Harmonised technical specifications
Fire reaction		NPD	
Water-proofing		Watertight at 2 kPa	
Water vapour transmission		Sd > 200 m	
Shock resistance		NPD	
Shear strength of joints		> 50 N/50mm	
Tensile strength	Maximum tensile force - longitudinal direction - transversal direction	> 300 N/50mm > 200 N/50mm	EN 13984 : 2013
	Elongation - longitudinal direction - transversal direction	> 20 % > 5 %	
Nail tear resistance - longitudinal direction - transversal direction		> 150 N > 150 N	
Durability	After ageing	Test successful	
	In alkaline environment	NPD	
Dangerous substances		A+	

## 8. Appropriate Technical Documentation and/or Specific Technical Documentation: **Not applicable**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Laurent THIERRY Chairman / Managing Director

At Limoux, on 21/12/2018



Avenue de Catalogne 11300 Limoux